

Hand formable (RG403) 50Ohm, 40GHz, 165°C, Ø2.5mm FEP jacket

SUCOFORM_86_FEP

Properties

- Hand-formable alternative to semi-rigid cables
- Small bend radius allows for space saving routing and packaging
- Performance comparable to semi-rigid cables
- FEP jacket



Construction			
Component	Material	Detail	Diameter
Centre conductor	Steel, Copper + Silver plated	Wire	0.53mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.65mm
Outer conductor	Copper, Tin plated	Tin soaked braid, 100%	2.1mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 3020 - rd	2.5 mm +/- 0.1 mm

Electrical data	
Impedance	50 Ω +/-2Ω
Operating frequency	≤ 40 GHz
Capacitance	95 pF
Velocity of signal propagation	71 %
Signal delay	4.7 ns/m
Screening effectiveness	100 dB at frequency 0.1 GHz ... 18GHz
Insulation resistance	100000000 MΩ*m
Inner conductor resistance	199 Ω/km
Operating Voltage (at sea level)	≤ 1.5 kV
Test voltage (50 Hz/1 min)	≤ 3 kV

Mechanical data	
Weight	approx. 18 g/m
Static bending radius	≥ 6 mm
Repeated bending radius	20 mm (bendings, up to 50)

Environmental data	
Operation temperature	-65 °C ... 165°C
Installation temperature	-20 °C ... 60°C
Flame propagation standard	IEC 60332-1 UL 1581 § 1080 (VW-1)

Hand formable (RG403) 50Ohm, 40GHz, 165°C, ø2.5mm FEP jacket

SUCOFORM_86_FEP

Environmental data	
Fire characteristics	contains halogene

Suitable connectors	
Cable group	Y16

Ordering information		
Item number	Item description	Available as assembly only
22511942	SUCOFORM_86_FEP	No

Power Matrix			
Calculation: typical Attenuation [formula: (a*f ^{0.5} + b*f)] and maximum Power CW [formula: (p/f ^{0.5})]			
a coefficient typical =	0.6283	b coefficient typical =	0.04
fmax =	40.0	P at 1 GHz =	280.0
Frequency GHz	Nom. attenuation (dB/m)	Nom. attenuation Max. (dB/ft)	CW power (W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.20	0.289	0.088	626
0.40	0.413	0.126	443
0.60	0.511	0.156	361
0.80	0.594	0.181	313
1.00	0.668	0.204	280
1.20	0.736	0.224	256
1.40	0.799	0.244	237
1.60	0.859	0.262	221
1.80	0.915	0.279	209
2.00	0.969	0.295	198
4.00	1.417	0.432	140
6.00	1.779	0.542	114
8.00	2.097	0.639	99
10.00	2.387	0.728	89
15.00	3.033	0.924	72
20.00	3.610	1.100	63
25.00	4.141	1.262	56
30.00	4.641	1.415	51
35.00	5.117	1.560	47
40.00	5.574	1.699	44

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P671 / Date of publication: 09.11.2023 / uncontrolled copy