



NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.
2. MATERIAL: INSULATOR - TEFLON PER ASTM D1710
 CRIMP SLEEVE - D.H.P. COPPER CDA ALLOY 122
 CONTACT - BERYLLIUM COPPER PER ASTM B196
 ALL OTHER METAL PARTS - BRASS PER ASTM B16.
3. FINISHES: CONTACT GOLD PLATE PER MIL-G-45204.
 CRIMP SLEEVE - SULFAMATE NICKEL PLATE PER MIL-P-27418
 ALL OTHER METAL PARTS SILVER PLATE PER QQ-S-365.

M39012/02-0503

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

TITLE: "N" CRIMP TYPE JACK FOR RG-142, 223, & 400/U CABLES

Drawn by BJM 12/23/02	Scale 2/1	Ckd. by	Engr Appd	FILE NAME: 1110018A00E-000T
-----------------------------	--------------	---------	-----------	--------------------------------

A	REVISED	12/28/18
-	OUTLINE	12/23/02
ALT.	REVISIONS	DATE

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02, ANGLES = ±1/2°, SURFACE FINISH = 63

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

CODE IDENT.-00795

1110-018-A00E