

# RG316D LSFH, 50 Ohm, 6 GHz, 105°C, ø3.16 mm, RADOX® jacket

## ENVIROFLEX\_316\_D

### Properties

- Halogen free alternative to RG cables
- Low smoke
- Ozone, UV and weathering resistance
- UL AWM style 3651
- CPR qualified



### Construction

Component	Material	Detail	Diameter
Centre conductor	Steel, Copper + Silver plated	Strand-07	0.54 mm
Dielectric	SPEX (Crosslink Foam PE)		1.53 mm
Outer conductor	Copper, Silver plated	Braid, 96%	1.99 mm
Outer conductor	Copper, Silver plated	Braid, 90%	2.44 mm
Jacket	RADOX	RAL 9005 - bk	3.16 mm +/- 0.08 mm

### Electrical data

Impedance	50 Ω +/-2Ω
Operating frequency	≤ 6 GHz
Capacitance	94.5 pF/m
Velocity of signal propagation	70.1 %
Signal delay	4.72 ns/m
Operating Voltage (at sea level)	≤ 1.3 kVrms
Voltage Rating UL	300 V
Test voltage (50 Hz/1 min)	≤ 3 kVrms

### Mechanical data

Weight	approx. 21 g/m
Static bending radius	≥ 5 mm
Repeated bending radius	30 mm (bendings, up to 3000)
Dynamic bending radius	≤ 30 mm
Abrasion test	MIL-T-81490 - §4.7.19 - prod. II - modified

### Environmental data

Operation temperature	-40 °C ... 105 °C
Installation temperature	-20 °C ... 60 °C
CPR class	Eca

## RG316D LSFH, 50 Ohm, 6 GHz, 105°C, ø3.16 mm, RADOX® jacket ENVIROFLEX\_316\_D

Environmental data	
Flame propagation standard	EN 60332-1-2
	UL 1581 § 1100
	EN 50305, 9.1.2
	FAR 25.869
Fire characteristics	free of halogenes, acc. standard IEC 60754
Smoke test	EN 61034-2
Ageing test	MIL-C-17 § 4.8.16
Cold bend test	MIL-C-17 § 4.8.19
UV resistance	IEC 60068-2-5, proc. C
Thermal stress test	IEC 61196-1 § 10.9

Suitable connectors	
Cable group	U4

Ordering information		
Item number	Item description	Available as assembly only
22512281	ENVIROFLEX_316_D	No

Power Matrix			
Calculation: typical Attenuation [ formula: (a*f^0.5 + b*f) ] and maximum Power CW [ formula: (p/f^0.5) ]			
a coefficient typical =	<b>0.7648</b>	b coefficient typical =	<b>0.1301</b>
fmax =	<b>6</b>	P at 1 GHz =	<b>110</b>
Frequency GHz	Nom. attenuation (dB/m)	Nom. attenuation (dB/ft)	CW power (W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.10	0.255	0.078	348
0.20	0.368	0.112	246
0.30	0.458	0.140	201
0.40	0.536	0.163	174
0.60	0.670	0.204	142
0.80	0.788	0.240	123
1.00	0.895	0.273	110
1.20	0.994	0.303	100
1.40	1.087	0.331	93
1.60	1.176	0.358	87
1.80	1.260	0.384	82
2.00	1.342	0.409	78
2.50	1.535	0.468	70
3.00	1.715	0.523	64
3.50	1.886	0.575	59
4.00	2.050	0.625	55
5.00	2.361	0.720	49
6.00	2.654	0.809	45

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P27708 / Date of publication: 08.08.2024 / uncontrolled copy