


MINI141 K-5, 2.9mm (male), 2.9mm (male), 50 Ohm, 40 GHz, 5 in, 127 mm

MINI141 K-5

Properties

- Applicable up to 40 GHz
- Part of the "bend-to-the-end" MINIBEND product family
- Direct replacement for 141 size Semi-Rigid cables
- Low loss PTFE dielectric
- Solderless cable junction



Product configuration

Type of cable	MINI141 (32022E)
Type description connector A	29094KCR-32-22
Type description connector B	29094KCR-32-22
Length	127 mm
	5 inch
Length type	Cable length

Electrical data

Impedance	50 Ω
Max. operating frequency	40 GHz
VSWR max	1.45
Propagation velocity	76 %

Mechanical data

Cable diameter	3.61 mm
Static bending radius	8.38 mm

Environmental data

Operation temperature	-55 °C ... 125 °C
-----------------------	-------------------

Ordering information

Item number	Item description
80336731	MINI141 K-5

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P38075 / Date of publication: 01.02.2024 / uncontrolled copy