

## RG400, 50 Ohm, 6 GHz, 200°C, Ø4.95 mm, FEP jacket

### RG\_400\_/U

#### Properties

- Mil standard RG cable
- Excellent RF performance for precision applications
- Suitable for use in applications up to 6 GHz
- Extended temperature range



Construction			
Component	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Strand-19	1 mm
Dielectric	PTFE (Polytetrafluoroethylene)		2.95 mm
Outer conductor	Copper, Silver plated	Braid, 97%	3.6 mm
Outer conductor	Copper, Silver plated	Braid, 94%	4.2 mm
Jacket	FEP (Fluorinated ethylene propylene)		4.95 mm +/- 0.1 mm

Electrical data	
Impedance	50 Ω +/-2Ω
Operating frequency	≤ 6 GHz
Capacitance	94 pF/m
Velocity of signal propagation	69 %
Signal delay	4.75 ns/m
Screening effectiveness	81 dB at frequency 0.001 GHz ... 6GHz
Insulation resistance	1000000000 MΩ*m
Inner conductor resistance	28.31 Ω/km
Operating Voltage (at sea level)	≤ 1.7 kVrms
Test voltage (50 Hz/1 min)	≤ 3.4 kVrms

Mechanical data	
Weight	approx. 64 g/m
Static bending radius	≥ 30 mm
Repeated bending radius	50 mm
Dynamic bending radius	< 75 mm

**RG400, 50 Ohm, 6 GHz, 200°C, Ø4.95 mm, FEP jacket**

RG\_400\_/U

Environmental data	
Operation temperature	-65 °C ... 200 °C
Installation temperature	-20 °C ... 60 °C
Flame propagation standard	IEC 60332-3
Fire characteristics	IEC 60332-1-2 contains halogene

Additional Information
MIL reference: M17/128-RG400

Suitable connectors	
Cable group	U11

Ordering information		
Item number	Item description	Available as assembly only
22510080	RG_400_/U	No

Power Matrix			
Calculation: typical Attenuation [ formula: (a*f^0.5 + b*f) ] and maximum Power CW [ formula: (p/f^0.5) ]			
a coefficient typical =	<b>0.3894</b>	b coefficient typical =	<b>0.0925</b>
fmax =	<b>6</b>	P at 1 GHz =	<b>365</b>
Frequency GHz	Nom. attenuation (dB/m)	Nom. attenuation (dB/ft)	CW power (W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.20	0.193	0.059	816
0.40	0.283	0.086	577
0.60	0.357	0.109	471
0.80	0.422	0.129	408
1.00	0.482	0.147	365
1.20	0.538	0.164	333
1.40	0.590	0.180	308
1.60	0.641	0.195	289
1.80	0.689	0.210	272
2.00	0.736	0.224	258
4.00	1.149	0.350	182
6.00	1.509	0.460	149

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P957 / Date of publication: 08.08.2024 / uncontrolled copy