

RG58, 50 Ohm, 1 GHz, 85°C, ø4.95 mm, PVC jacket

RG_58_C/U

Properties

- Mil standard RG cable
- Excellent RF performance for precision applications
- Suitable for use in application up to 1 GHz



Construction			
Component	Material	Detail	Diameter
Centre conductor	Copper, Tin plated	Strand-19, 96%	0.9 mm - 0.15 mm
Dielectric	PE (Polyethylene)		2.95 mm
Outer conductor	Copper, Tin plated	Braid, 96%	3.6 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	4.95 mm +/- 0.15 mm

Electrical data	
Impedance	50 Ω +/-2Ω
Operating frequency	≤ 1 GHz
Capacitance	101 pF/m
Inductance	0.254 μH/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Screening effectiveness	38 dB at frequency 0.0001 GHz ... 1GHz
Insulation resistance	100000000 MΩ*m
Inner conductor resistance	34.5 Ω/km
Operating Voltage (at sea level)	≤ 2.5 kVrms
Test voltage (50 Hz/1 min)	≤ 5 kVrms

Mechanical data	
Weight	approx. 37 g/m
Static bending radius	≥ 25 mm
Repeated bending radius	50 mm

RG58, 50 Ohm, 1 GHz, 85°C, Ø4.95 mm, PVC jacket
 RG_58_C/U

Environmental data	
Operation temperature	-25 °C ... 85 °C
Installation temperature	-20 °C ... 60 °C
Fire characteristics	contains halogene

Additional Information
MIL reference: M17/183-00001 (former reference: M17/28-RG058)

Suitable connectors
Cable group U7

Ordering information		
Item number	Item description	Available as assembly only
22510015	RG_58_C/U	No

Power Matrix			
Calculation: typical Attenuation [formula: (a*f^0.5 + b*f)] and maximum Power CW [formula: (p/f^0.5)]			
a coefficient typical =	0.3455	b coefficient typical =	0.2373
fmax =	1.0	P at 1 GHz =	105.0
Frequency	Nom. attenuation	Nom. attenuation	CW power
GHz	(dB/m)	(dB/ft)	(W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.10	0.133	0.041	332
0.20	0.202	0.062	235
0.30	0.260	0.079	192
0.40	0.313	0.095	166
0.60	0.410	0.125	136
0.80	0.499	0.152	117
1.00	0.583	0.178	105

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
 DOCUMENT PIM-P956 / Date of publication: 02.09.2024 / uncontrolled copy