

ATTENUATORS


SMA, up to 18 GHz, 5 Watts

SPECIFICATIONS:

Models: 18B5W-XX, 18B5W-XXF & 18B5W-XXM


RoHS
Compliant

Electrical:	
Frequency Range _____	DC - 18 GHz
Standard Freq. Values _____	6, & 18 GHz
Standard dB Values* _____	0 - 10, 12, 15, 20, 30, & 40 dB
Attenuation Accuracy _____	In 1 dB Increments
0 - 6 dB _____	±0.3 dB
7 - 20 dB _____	±0.5 dB
21 - 30 dB _____	±0.75 dB
40 dB _____	±1.5 dB
VSWR	
DC - 4 GHz _____	1.15:1 Max.
4 - 8 GHz _____	1.20:1 Max.
8 - 12.4 GHz _____	1.25:1 Max.
12.4 - 18 GHz _____	1.35:1 Max.
Input Power _____	5 Watts Avg. @ 25°C
	Derated Linearly to 1 Watt @ +125°C
Impedance _____	50 Ohms
Operating Temp Range _____	-65°C to +125°C
Mechanical:	
SMA Connectors _____	Passivated Stainless Steel
	Mates with MIL-STD-348
Conductors _____	Gold Plated Beryllium Copper
Housing _____	Anodized Aluminum



Connector Configuration	LENGTH	
	0 - 30 & 40dB	
	Inches	Millimeters
Male/Female	1.20 ±.05	[30.5 ±1.3]
Male/Male	1.33 ±.05	[33.8 ±1.3]
Female/Female	1.06 ±.05	[26.9 ±1.3]

HOW TO ORDER:



Ordering Examples:

Model Number: **6B5W-20**
DC -6 GHz, 20 dB; SMA - Male/Fem

Model Number: **18B5W-06F**
DC - 18 GHz, 6 dB; SMA - Fem/Fem

Model Number: **18B5W-03M**
DC - 18 GHz, 3 dB; SMA - Male/Male

Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.

*Other dB values, units that operated over a more specific frequency band and/or offer very low return loss (VSWR) are also available.

XXB5W-ATT: REV N (M)



Aeroflex / Inmet, Inc. • 300 Dino Drive, Ann Arbor, MI 48103 • U.S.A.
888-244-6638 or 734-426-5553 • FAX: 734-426-5557
www.aeroflex-inmet.com • inmet-sales@aeroflex.com